

FORMULA: C₄H₁₁N

MOL WT: 73.14

DESCRIPTION

Dimethylethylamine is a low molecular weight tertiary amine. It is generally used in the automotive casting industry. The product is colorless substance and has a strong ammoniacal odor.

APPLICACTIONS

Chemical intermediates, catalysis, polymer formulations, rubber chemicals, resin curing in foundries (Cold Box process).

SPECIFICATIONS

TEST METHOD

Purity, wt. %	99.2	Min.	MP-401
Water, wt. %	0.2	Max.	MP-403
Color, Pt-Co	20	Max.	MP-408
Impurities:			MP-401
Ethylmethamine, wt. %	0.3	Max.	
Diethylmethamine, wt. %	0.3	Max.	
Density @ 20°C, g/mL	0.676 ± 0.02		MP-404

Notes:

N/A

AVAILABILITY

In bulk, 300 kg tanks (661.39 lb) or drums containing 200 L (52.85 gal).



Unidad Industrial Irapuato

SALES SPECIFICATION

EVCI-410

DIMETHYLETHYLAMINE

08/22/24

2 of 2

Revision

03

Headquarters: Av. Paseo de las Palmas 781, Piso 2, Colonia Lomas de Chapultepec III Sección, Miguel Hidalgo, C.P. 11000, Ciudad de México. Tel. 55 2789-2200

IRAPUATO Plant: Av. Salamanca 1843 Cd. Industrial de Irapuato C.P. 36540 Irapuato, Gto., Tel. 462 622 5087 Fax 462 622 5088

Website

www.grupoidesa.com

Email Commercial: pedidosidesa@idesa.com.mx **Quality:** Calidad.Idesa@idesa.com.mx